



St-Chrysostome Demolition Derby

Pick-Up Provincial Championship

<http://demolition-st-chrysostome.org>

All judges' and officials' decisions are final and definitive.

Have good sportsmanship and common courtesy; our goal is to put on a **good show.**

A1 Any driver who is under the influence of drugs or alcohol will be disqualified.

A2 Participants must be at least 18 years old. We allow drivers who are 16 years old **before the event** when they present a **health insurance card** and permission **signed by a parent.**

During the derby:

A3 An approved safety helmet must be worn **throughout the entire derby.** If your car does not have a windshield, it is mandatory to wear a **helmet with a visor during the entire derby. If not, you will be disqualified.** Drivers must wear long-sleeve shirts and long pants.

A4 If your vehicle catches fire, the derby is stopped and the firefighters will put it out. If after the derby re-starts and your vehicle catches fire a second time, **you will be automatically disqualified.** If there is a leak in the gas tank, **you will be disqualified.** If the driver's seat, the post supporting the driver's seat or the metal reinforcement protecting the driver's door collapses from impact, **you will be disqualified. A functional seatbelt is mandatory.**

A5 If you hit a car on the driver's side without making any obvious attempt to avoid it, **you will automatically be disqualified.**

A6 You have a maximum of two minutes to hit another car. If your vehicle is stopped, you have two minutes to re-start it and hit another car.

A7 A vehicle deemed too damaged or too dangerous for the safety of the driver may be disqualified by the officials. The driver who is the last to hit a non-disqualified car will be the winner.


Vehicle Preparations

REQUIREMENT

B1 Remove all finishings from the vehicle (chrome, mirrors, door handles, mouldings, antenna, window panes, headlights and taillights). The back seat must be removed and **the interior of the vehicle rid of all finishings and debris.**

B2 You must pierce two holes each at least 15 inches in diameter in the hood and **remove the sheet metal.** This will help the firefighters in case of a fire.

B3 All the doors must be chained with a maximum of **two** chains per door. Only the driver's door may be welded shut and **must be protected by a reinforced metal or pipe of about four inches,** fixed by **four bolts** that are at least half an inch in diameter. The reinforced metal must longer than the driver's door by **about one foot** in front and **one foot** behind. (See C5)



B4 The front doors of each side must be free of any writing. They are reserved for the car's number. The number must be at least **24 inches tall and be legible from afar.** The windshield must not be obstructed by drawings or advertising logos.

B5 The driver's seat must be in good condition and reinforced with **a pole fixed to the floor** by two **bolts** in the rear. It should be no more than **one foot** taller than the roof.

B6 There can only be 15 litres, at most, of gas in the tank.

B7 Over-sized tires are not allowed. Spinning rims are not allowed. **Lead must be removed from the inside and outside on all wheels.**

B8 For ecological reasons, **replace the radiator antifreeze with water.**

B9 AIRBAGS MUST BE REMOVED OR MUST REMAIN INTACT. NEVER CUT THE AIRBAG OUT.

PERMISSION

B10 You may protect the battery with a metal support or move it to the inside of the vehicle. However, it must be at least **two feet** away from the gas tank. It is suggested that you put it in the passenger seat. There, it must be **very solidly fixed so that it will not move.**

B11 You may move the gas tank to the inside of the vehicle, but only to where the back seat would be. This must be **very solidly fixed so that it will not move.**

B12 You may replace the original gas tank with another type approved for motorized vehicles (boat tank, snowmobile tank). This must be **equipped with an adequate cap. No leaks will be tolerated. No refueling canisters.** If you use another approved type, you must remove the original tank.

B13 You may chain, bolt down or weld the hood, trunk and bumpers, which must all be original. Bolts must be no more than one inch in diameter and must not be connected to each other. There can be at **most six tarots per rod** and there must be **at least six inches between each rod washer. No exaggerations.**

DEFENSE

B14 The radiator and its reserve tank may not be moved; however, it can be removed. Iron radiators will not be allowed.

B15 It is forbidden to install a transmission oil cooler inside the vehicle.

B16 It is forbidden to reinforce the vehicle in any way other than as mentioned above.

B17 IT IS FORBIDDEN TO PAINT OR CAMOUFLAGE THE FRAME.

B18 No bolts should be sticking out of the sides of the vehicle by more than **two** inches, nor out of the hood or trunk by more than **six** inches.

B19 Vehicles cannot be reinforced with metal. **REPAIRS OR WELDING ON THE FRAME WILL NOT BE ACCEPTED.** Trailer coupling and reinforcements of any kind must be removed.

B20 Metal straps with holes may not be used to attach the battery or gas tank.

B21 The hood may only be attached to the bumper with chains.

B22 FRONT AND REAR BUMPERS MUST BE A REASONABLE HEIGHT OFF THE GROUND.

B23 IT IS FORBIDDEN TO MODIFY THE ORIGINAL SHAPE OF A STATION WAGON.

PLEASE NOTE THAT AS OF 2017, ANY CHRYSLER IMPERIAL MADE BEFORE 1970 OR THE FRAME OF THIS MODEL ON ANOTHER BODY WILL NOT BE ACCEPTED.

Pick-up and Mini Pick-up Preparation

C1 All rules listed in "B".

C2 It is forbidden to make a cage inside the pick-up (style stock car).

C3 The box must be attached to the frame with reinforced metal. This must be fixed in the box from one foot from the inside to one foot from the tail gate by **six** bolts. Furthermore, extremities must be closed to form a rectangle. No crossbars.

C4 A tail gate is mandatory. The box must be connected to the tail gate by two angle irons each fixed by at least four half-inch bolts. For Suburban-type pick-ups, the rear doors must be chained with the roof.

C5 THE BOX MUST HAVE ITS ORIGINAL SHAPE.



C6 The driver's door must be protected with reinforced metal or a pipe that is at least **four inches**, fixed by at least **four half-inch** bolts. The reinforced metal must be taller than the driver's door by **about one foot** in front and **one foot** in the rear.

C7 Bumpers must be the originals. No car bumpers will be tolerated on a truck. They may be welded to the frame. It is forbidden to reinforce corner fasteners.

C8 4x4's are allowed provided that the front axle is ineffective.

Van and Mini-Van Preparation

D1 All the rules listed in "B".

D2 The driver's door must be protected with reinforced metal or a pipe that is at least **four inches**, fixed by at least **four half-inch** bolts. The reinforced metal must be longer than the driver's door by about **one foot** in front and **one foot** behind.

D3 There must be large **openings** on each side and at the back of the same width as a window for good vision.

D4 All doors must be chained to the roof except for the driver's and front passenger's doors.

D5 The engine cover must be kept.