

## MASS MOTORSPORT

Rules Derby Demolition season 2024

vehicle regulations: general regulations

- 1-The seals must be removed from all wheels.
- 2-You must remove all interior and exterior trim, lights, and windows. The windshield is tolerated.
- 3-Remove all airbags.
- 4-The vehicle must be clean, free of debris or pieces of glass.
- 5-You must remove the spare tire.
- 6-Mandatory brake (possibility of a brake test before the consolation/final race included)
- 7-Two 12-inch holes or 1 24-inch hole must be drilled on the hood to facilitate the work of firefighters.
- 8-Trailer hitches or reinforcement of any kind must be completely removed.
- 9-All vehicle doors must be chained.
- 10-The number of your vehicle must be legibly written on each side of the vehicle (12 inches minimum).
- 11-The driver's seat must be in good condition and must be reinforced by a post securely attached to the floor and roof. If the seat breaks you will be disqualified.
- 12-Replace the radiator antifreeze with water. (With the exception of the winter derby)
- 13-Radiator: In stock classes the radiator must be original and cannot be moved. It can be replaced by a hose only for repair after a race but no metal tank. Iron radiators are permitted in certain classes. Consult the specific regulations for each class for details.
- 14-It is prohibited to reinforce the vehicle except as mentioned in the regulations. No matter how, with cement or metal (except repair plates in applicable classes)
- 15-Vehicles must be completed and ready to race upon arrival.
- 16-The fuel tank is accepted under the vehicle, if it is placed before the axle.
- 17-The battery and the fuel tank can be moved inside the vehicle. They must be securely fixed. If they move or the tank flees you will be disqualified without exception. No refueling canister.
- 18-The driver's door must be reinforced with a metal beam on the outside of the door. It must extend approximately 1 foot from each side of the door and securely fastened with at least 4 bolts of at least 1/2-inch diameter. 1 in the fender, 2 in the driver's door and 1 in the door or rear panel. The ends of the beam must be cut at an angle and the bolts must not protrude from the beam. If the beam falls during the race, you will be disqualified.

19-No chain wrapped around the bumper

20-Nonimperial full frame

21-No bolts connect them together

22-To have access to consolation, the car must have participated in its regular race to have the right to go to consolation

23-It is obligatory to wear long sleeves and long pants when running

24-Any unmentioned modification made to the vehicle may cause a refusal of inspection

**Failure to comply with one of these rules may result in refusal of inspection.**

**The judges' decision is final.**

**Happy season!!!**